

# Wear kits

Wear parts in Flygt dewatering pumps are designed for long-lasting performance in tough and abrasive applications. Thanks to advanced engineering, unique materials and precise manufacturing, the unique wear parts minimize power consumption, too.



## Wear part kits and hydraulic repair kits

### Simplify spare parts handling and pump repair work

Flygt wear part kits and hydraulic repair kits are available for a wide range of Flygt dewatering pumps, including 2610 through 2670 and 2052 through 2151. A wear part kit includes an impeller, suction cover, O-ring and fasteners for basic repair of the pump's hydraulic end. For a more extensive repair of the hydraulic end, the wear part kits can be combined with a hydraulic repair kit, which contains a seal housing cover, diffuser and shock absorbers.

Flygt wear part kit

*Impeller*



*Suction cover*



*O-ring and fasteners*



Flygt hydraulic repair kit

*Seal housing cover*



*Diffuser*



*Shock absorbers*



# Impeller

## Durable closed impeller design

The durable closed impeller design with its solid upper cover disc and balanced hydraulic axial load assures low bearing loads and minimizes the risk of impeller cracks. This also leads to less wear of the seal housing.

## Hard-Iron™ for outstanding wear resistance

Flygt dewatering pump impellers are made from a unique alloy with 25% chromium content and a hardness of HRC 60. Accelerated wear tests prove that Flygt Hard-Iron hydraulic components continue to operate efficiently and with minimal wear under extremely tough conditions.

## Patented high head geometry

The impact angle of abrasives on the leading edges is flattened, which reduces wear. The leading edges also tolerate extensive wear before performance is affected.

## Accurate casting tolerances and well-balanced design

Reliable, high-precision casting processes ensure that the impeller and the Dura-Spin™ function deliver the required high pumping performance. In addition, the precise, well-balanced impeller minimizes the risk of vibration and high bearing loads.

## Improved shaft and impeller assembly

Our design enables easy assembly and disassembly without keyway stress concentrations, thereby minimizing the risks of fatigue cracks that cause shaft and impeller damage.

## High sustained efficiency with minimized power consumption and wear

At Flygt, we have developed design programs and engineering tools that iterate against CFD simulations to achieve the highest possible pumping efficiency and low power consumption without compromising wear resistance or pumping performance.

## Easy gap adjustment and impeller disassembly

The impeller sleeve facilitates easy adjustment of the gap between the impeller and insert ring and creates tight clearances between the impeller and suction cover to ensure high efficiency. In addition, the impeller sleeve ensures easy disassembly of the impeller using standard tools only. Tightening the impeller sleeve unit with a hexagon bit adapter creates a shaft end pressure that pushes the impeller off the shaft.



*Closed impeller design.*



*Patented high head geometry.*



*High-precision casted suction cover.*

*Well-balanced impeller.*



*Tight tolerances.*



*Impeller sleeve.*

---

## Suction cover

### Patented Dura-Spin™ technology

The back vanes of the unique closed dewatering pump impeller and the suction cover with Dura-Spin grooves work together, sweeping abrasive particles away from the seal cavity. Thanks to this system, the gap between the impeller neck and suction cover is only exposed to clean water, which results in extremely low wear and extended seal life.



*Patented Dura-Spin technology.*

---

## Seal housing cover and diffuser

### High quality lining

The reliable, high-precision priming process ensures superior adhesion and minimizes the risk of the rubber separating from the metal body.

### Sustained wear resistance and precise geometries

Stable CFD-calculated geometries, high-precision casting processes and durable rubber properties provide sustained wear resistance and accurate performance. The seal housing cover is also protected from corrosion as no bare metal is exposed to the pumped media.



*The seal housing cover and diffuser.*



# Xylem |'zīləm|

- 1) The tissue in plants that brings water upward from the roots;
- 2) a leading global water technology company.

We're 12,000 people unified in a common purpose: creating innovative solutions to meet our world's water needs. Developing new technologies that will improve the way water is used, conserved, and re-used in the future is central to our work. We move, treat, analyze, and return water to the environment, and we help people use water efficiently, in their homes, buildings, factories and farms. In more than 150 countries, we have strong, long-standing relationships with customers who know us for our powerful combination of leading product brands and applications expertise, backed by a legacy of innovation.

For more information on how Xylem can help you, go to [www.xyleminc.com](http://www.xyleminc.com)



**xylem**

Let's Solve Water

Xylem, Inc.  
14125 South Bridge Circle  
Charlotte, NC 28273  
Tel 704.409.9700  
Fax 704.295.9080  
855-XYL-H2O1 (855-995-4261)  
[www.xyleminc.com](http://www.xyleminc.com)

Flygt is a trademark of Xylem Inc. or one of its subsidiaries.  
© 2015 Xylem, Inc. MAY 2015